-	, Tourney
Form 113-5M-12-60 ExaminedAUG 1 1978 7/15	
	RT OF WELL DRILLER Application No. 26597 (18-163
Inspection Sheet	STATE OF UTAH Application No. 2001/(18-70)
Copied	Coordinate No. (C-19-19)26 A
GENERAL STATEMENT: Report of well driller is hereby (This report shall be filed with the State Engineer within a reports constitutes a misdemeanor.)	by made and filed with the State Engineer, in accordance with the laws of U 30 days after the completion or abandonment of the well. Failure to file s
(1) WELL OWNER:	(12) WELL TESTS: Drawdown is the distance in feet the water level is
Name Corp. of the Pres. of the Aaronic Order Address P.D. Box 7095 Murray Ut 84107	ered below static level. Was a pump test made? Yes No 🔼 If so, by whom?
	Yield:gal./min. withfeet drawdown after
(2) LOCATION OF WELL:	"
County Millard Ground Water Basin (leave blank)	Bailer test 123 gal./min. with 5 feet drawdown ever 2 h
South 1320 feet, West 1320 feet from NW Corner	Arterian flow g.p.m. Date Temperature of water 55° Was a chemical analysis made? No X Yes
of Section 26 T 19 R 19 TSLBM (strike	Temperature of water Was a chemical analysis made? No X Yes
out words not needed)	(10) The state of mall
(3) NATURE OF WORK (check): New Well W	Depth drilled 200 feet. Depth of completed well 200
Replacement Well December Repair Abandon	Index REMARKS wake
f abandonment, describe material and procedure:	
	DEPTH MATERIAL
(A) NATURE OF UCE ()	
(4) NATURE OF USE (check):	REMARKS
prigation Mining Other Test Well	[[[[[[[[[[[[[[[[[[[
5) TYPE OF CONSTRUCTION (check):	0 3 XX
totary Dug Jetted D	2 E XX
able Driven Bored	5 7 X
6) CASING SCHEDULE: Threaded Welded	13 16 V
"Diam, from O feet to 193 feet Gage 375	16 20 X
" Diam from feet to feet Gage Diam from feet to feet Gage	26 26 X
ew 🕱 Reject 🗆 Used 🗆	26 30 XX
7) PERFORATIONS.	33 35 X
ype of perforator used Mills	35 38 X
to of perforations 1/2 inches by 2/2 inches by 1/2	38 41 X X 41 49 X
324 perforations to 147	49 53 XX
perforations from	53 60 X
perforations from feet to feet	60 63 X
perforations from feet to feet	70 72 X
S) SCREENS: Well acreen installed? Yes No X	72 75 X X X X X X X X X X X X X X X X X X
nufacturer's Name	80 88 X Chalky White
sm. Slot size Set from ft. to.	88 92 X fine Sand
m. Slot size Set from ft. to	92 110 X 110 112 X
) CONSTRUCTION:	112 117 X
s well gravel packed? Yes No Size of gravel:	117 122 X X
s a surface seal provided? Yes No	122 125 X X X X X X X X X X X X X X X X X X X
To what depth? 15	130 133 X
any strata contain unusable water? Yes No by	[33]140 X
e of water: Depth of strata	140 143 X Quicksand water status
hod of sealing strata off:	Work started 1/24 70 2/23/
Alleface cooling and 2	(14) PUMP:
th semantal in the	Manufacturer's Name
	Depth to pump or bowles feet
ic level 2 feet below land surface Date 3/24/78	Well Driller's Statement:
sian pressure	This well was drilled under my supervision, and this report is true the best of my knowledge and belief.
	Name Scott L. Anderson
Controlled by (aback)	Address ESKDale Garrison Utah 94708
Sep. Plug No Control	(Signed) Los J. J. State 17001